

Compressed air station **SD 10** to **SD 29-2** Compressed air centre **SD 10-** to **SD 29-2-**

Effective free air delivery: 0.91 – 3.45 m³/min, 32 – 122 cfm

Pressure range: 8 – 13 bar, 115 – 190 psig

Motor range: 7.5 – 22 kW, 10 – 30 HP



Compressed air station **SD**

Screw compressor
with integral refrigerant dryer



Compressed air centre **SD-**

Screw compressor
with refrigerant dryer
mounted on horizontal receiver



SD 10	8	115	1.18	42	7.5	10	SD 10 to SD 15	super-silenced ultra-silenced	975 x 700 x 1265 975 x 700 x 1495	260 275
	10	150	1.06	39	7.5	10				
	13	190	0.91	32	7.5	10				
SD 15	8	115	1.65	58	11.0	15	SD 20-2	super-silenced ultra-silenced	1200 x 850 x 1500 1200 x 850 x 1850	400 425
	10	150	1.45	51	11.0	15				
	13	190	1.25	44	11.0	15				
SD 20-2	8	115	2.57	91	15.0	20	SD 24-2 to SD 29-2	super-silenced ultra-silenced	1200 x 850 x 1500 1200 x 850 x 1850	425 450
	10	150	2.66	94	18.5	25				
	13	190	2.26	80	18.5	25				
SD 24-2	8	115	3.05	108	18.5	25	SD 29-2			
	10	150	3.11	110	22.0	30				
	13	190	2.57	91	22.0	30				

BOGE				Effective free air				Receiver options		BOGE		Dimensions		Weight
BOGE Model	Receiver volume Litres	Max. pressure**		Effective free air delivery*		Motor power		Receiver options Litres	BOGE Model	Dimensions W x D x H mm		Weight kg		
		bar	psig	m ³ /min	cfm	kW	HP							
SD 10-	350	8	115	1.18	42	7.5	10	500, 750	SD 10- to SD 15- super-silenced from to ultra-silenced from to	1650 x 790 x 1550 2000 x 935 x 1760 1650 x 790 x 1750 2000 x 935 x 1990	400 520 415 535			
		10	150	1.06	39	7.5	10	500, 750						
		13	190	0.91	32	7.5	10	500, 750						
SD 15-	350	8	115	1.65	58	11.0	15	500, 750	SD 20-2- to SD 29-2- super-silenced from to ultra-silenced from to	2000 x 950 x 1950 2000 x 950 x 1950 2000 x 950 x 2300 2000 x 950 x 2300	670 695 695 720			
		10	150	1.45	51	11.0	15	500, 750						
		13	190	1.25	44	11.0	15	500, 750						
SD 20-2-	750	8	115	2.57	91	15.0	20							
		10	150	2.24	80	15.0	20							
		13	190	1.90	67	15.0	20							
SD 24-2-	750	8	115	3.05	108	18.5	25							
		10	150	2.66	94	18.5	25							
		13	190	2.26	80	18.5	25							
SD 29-2-	750	8	115	3.45	122	22.0	30							
		10	150	3.11	110	22.0	30							
		13	190	2.57	91	22.0	30							

* Free air delivery for the complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound level as per PN8NTC2.3 from 72 dB(A)

** Max. pressure of the compressor